

# ***THUNDERER***

---

## **THE DRIVING FORCE IN TIRES**



## **PRODUCT CATALOG**



# THUNDERER

## THE DRIVING FORCE IN TIRES

### COMPLETE LINE

Thunderer tires, a complete full line brand that includes both speciality and broad line applications for passenger / performance SUV / crossovers / light truck / trailers and more.

# +5

# 50+ NEW PRODUCTS NEW SIZES IMPROVED UTQG's

### STATE-OF-THE-ART

Manufactured in state-of-the-art factories in Thailand with world-class design / finish / sizing.

### “NO QUESTIONS ASKED”

Our “25/365 NO QUESTIONS ASKED” warranty covers both road hazard and mileage warranties.

### MARKETING SUPPORT

Intelligent and relevant marketing materials that build sales and awareness.

## JOIN FORCES

Imported exclusively by American Omni.  
Distributed thru authorized resellers worldwide.



## MACH IV

**R302 | ULTRA HIGH PERFORMANCE**

Aggressive yet sophisticated, the Mach IV offers the best of comfort and performance. Designed with Thunderer's unique directional tread pattern handles aggressive driving and quiet performance. H, V, W and WXL rated for proper fitment applications.

### 60,000 MILES | NO QUESTIONS ASKED

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
155/80R13	79H	10	22.8	6.2	965@44	500AA	TH0155
205/70R15	96T	10	26.3	8.2	1565@44	500AA	TH0156
195/65R15	91H	10	25.0	7.9	1355@44	500AA	TH0147
205/65R15	94H	10	25.5	8.2	1480@44	500AA	TH0148
185/60R15	84V	10	23.7	7.4	1100@44	500AA	TH0150
195/60R15	88V	10	24.2	7.9	1230@44	500AA	TH0152
205/60R15	91V	10	24.7	8.2	1355@44	500AA	TH0154
215/60R15	94V	10	25.2	8.7	1480@44	500AA	TH0156
225/60R15	96V	10	25.6	9.0	1565@44	500AA	TH0158
185/55R15	82V	10	23.0	7.6	1050@44	500AA	TH0160
195/55R15	85V	10	23.4	7.9	1140@44	500AA	TH0162
205/55R15	88V	10	23.9	8.4	1230@44	500AA	TH0172
195/50R15	82V	10	22.7	7.9	1050@44	500AA	TH0173
205/60R16	92V	10	25.7	8.2	1390@44	500AA	TH0164
215/60R16	95V	10	26.1	8.7	1520@44	500AA	TH0166
225/60R16	98V	10	26.6	9.0	1655@44	500AA	TH0168
235/60R16	100V	10	27.1	9.5	1765@44	500AA	TH0170
185/55R16	83V	10	24.0	7.6	1070@44	500AA	TH0174
195/55R16	87V	10	24.4	7.9	1200@44	500AA	TH0176
205/55R16	91V	10	24.9	8.4	1355@44	500AA	TH0177
215/55R16XL	97V	10	25.3	8.9	1609@50	500AA	TH0169
225/55R16XL	99V	10	25.8	9.2	1710@50	500AA	TH0167
195/50R16XL	88V	10	23.7	7.9	1230@50	500AA	TH0157
225/50R16	92V	10	24.9	9.2	1390@44	500AA	TH0159
215/60R17	96T	10	27.2	8.7	1565@44	500AA	TH0161
215/55ZR17	94W	10	26.3	8.9	1480@44	500AA	TH0178
205/50ZR17XL	93W	10	25.1	8.4	1435@50	500AA	TH0187
215/50ZR17	91W	10	25.5	8.9	1355@44	500AA	TH0179
225/50ZR17	94W	10	25.9	9.2	1480@44	500AA	TH0180
215/45ZR17	87W	10	24.7	8.4	1200@44	500AA	TH0188
225/45ZR17XL	94W	10	25.0	8.9	1480@50	500AA	TH0181
225/45ZR18XL	95W	10	25.9	8.9	1520@50	500AA	TH0182
225/40ZR18XL	92W	10	25.1	9.1	1390@50	500AA	TH0183
235/40ZR18XL	95W	10	25.4	9.5	1520@50	500AA	TH0184
235/35ZR19XL	91W	10	25.5	9.5	1355@50	500AA	TH0185
265/30ZR19XL	93W	10	25.3	10.7	1435@50	500AA	TH0186





MACH III R702 I  
ULTRA HIGH PERFORMANCE

Aggressive directional tread design offers superior handling in all weather conditions. The solid continuous center rib provides stability at higher speeds and during hard braking. V and W rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
205/50ZR16	87W	10	24.1	8.4	1200@44	500AA	TH0130
205/45ZR16XL	87W	10	23.2	8.1	1200@50	500AA	TH0131
225/55ZR17	97W	10	26.8	9.2	1610@44	500AA	TH0134
235/55R17	99H	10	27.2	9.7	1710@44	500AA	TH0135
205/50R17	89V	10	25.1	8.4	1280@44	500AA	TH0136
205/45ZR17XL	88W	10	24.3	8.1	1234@50	500AA	TH0132
215/45ZR17	87W	10	24.7	8.4	1200@44	500AA	TH0133
235/45ZR17XL	97W	10	25.4	9.3	1610@50	500AA	TH0137
245/45R17XL	99W	10	25.7	9.6	1710@50	500AA	TH0138
205/40R17XL	84W	10	23.5	8.4	1100@50	500AA	TH0139
225/45ZR18XL	95W	10	25.9	8.9	1520@50	500AA	TH0141
235/45R18XL	98W	10	26.3	9.3	1655@50	500AA	TH0143
245/45ZR18XL	100W	10	26.7	9.6	1765@50	500AA	TH0144
245/40ZR18XL	97W	10	25.7	9.8	1610@50	500AA	TH0145
235/55R19	101V	10	29.2	9.7	1820@44	500AA	TH0149
225/30R20XL	85W	10	25.4	9.1	1140@50	500AA	TH0151
245/35R20XL	95W	10	26.8	9.8	1520@50	500AA	TH0153



MACH II R301 I  
HIGH PERFORMANCE

Great handling performance-rated tire with a split center groove for stability at higher speeds. Mild directional tread pattern offers dependable traction in wet and dry conditions. H or V rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
195/65R15	91H	10	25.0	7.9	1355@44	500AA	TH0074
205/65R15	94H	10	25.5	8.2	1477@44	500AA	TH0080
205/60R15	91V	10	24.7	8.2	1356@44	500AA	TH0077
185/55R15	82V	10	23.0	7.6	1047@44	500AA	TH0060
195/55R15	85V	10	23.4	7.9	1135@44	500AA	TH0068
195/50R15	82V	10	22.7	7.9	1047@44	500AA	TH0058
215/60R16	95V	10	26.1	8.7	1521@44	500AA	TH0096
205/55R16	91V	10	24.9	8.4	1356@44	500AA	TH0090
215/55R16XL	97V	10	25.3	8.9	1609@50	500AA	TH0092
225/55R16	95V	10	25.8	9.2	1521@44	500AA	TH0094



MACH I R201 I  
PREMIUM TOURING

Good handling, quiet-running 5-rib design. Long-wearing radial built to last for small and midsize vehicles. T, H and V rated for proper fitment applications.

60,000 MILES | NO QUESTIONS ASKED

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
165/70R13	79T	10	22.1	6.7	963@44	500AA	TH0015
175/70R13	82T	10	22.7	7.0	1047@44	500AA	TH0017
185/70R13	86H	10	23.2	7.4	1168@44	500AA	TH0021
165/65R13	77T	10	21.4	6.7	908@44	500AA	TH0011
175/70R14	84H	10	23.7	7.0	1102@44	500AA	TH0025
185/70R14	88H	10	24.3	7.4	1234@44	500AA	TH0022
195/70R14	91H	10	24.8	7.9	1356@44	500AA	TH0049
205/70R14XL	98H	10	25.4	8.2	1655@50	500AA	TH0040
175/65R14	82H	10	23.0	7.0	1047@44	500AA	TH0031
185/65R14	86H	10	23.5	7.4	1168@44	500AA	TH0042
185/60R14	82H	10	22.8	7.4	1047@44	500AA	TH0037
195/60R14	86T	10	23.2	7.9	1160@44	500AA	TH0041
215/70R15	98H	10	26.9	8.7	1655@44	500AA	TH0043
185/65R15	88H	10	24.5	7.4	1234@44	500AA	TH0055
195/65R15	91H	10	25.0	7.9	1355@44	500AA	TH0044
205/65R15	94H	10	25.5	8.2	1480@44	500AA	TH0045
215/65R15	96H	10	26.0	8.7	1565@44	500AA	TH0057
185/60R15	84H	10	23.7	7.4	1100@44	500AA	TH0046
195/60R15	88V	10	24.2	7.9	1234@44	500AA	TH0050
205/60R15	91H	10	24.7	8.2	1355@44	500AA	TH0047
215/60R15	94H	10	25.2	8.7	1480@44	500AA	TH0048
225/60R15	96H	10	25.6	9.0	1565@44	500AA	TH0051
205/65R16	95H	10	26.5	8.2	1520@44	500AA	TH0052
215/65R16XL	102H	10	27.0	8.7	1875@50	500AA	TH0053
235/65R16	103T	10	28.0	9.5	1930@44	500AA	TH0054
205/60R16	92H	10	25.7	8.2	1390@44	500AA	TH0056
215/60R16	95H	10	26.1	8.7	1520@44	500AA	TH0076
225/60R16	98H	10	26.6	9.0	1655@44	500AA	TH0078
235/60R16	100H	10	27.1	9.5	1765@44	500AA	TH0079
205/55R16	91H	10	24.9	8.4	1355@44	500AA	TH0081
215/65R17	99T	10	28.0	8.7	1710@44	500AA	TH0082
215/55R17	94H	10	26.3	8.9	1480@44	500AA	TH0083
225/50R17	94H	10	25.9	9.2	1480@44	500AA	TH0084



# RANGER A/T

## R404 | PREMIUM ALL-TERRAIN

Unique tread design maximizes traction edges for excellent handling on- and off-road. Closed shoulder ensures confident handling in all conditions. Engineered for light truck applications requiring 6 and 10 ply ratings. S and T rated for proper fitments.



S-T RATED • 6-10 PLY • LT-XL

# 36 SIZES

COMPLETE SIZE RANGE

# 15"/20"

FOR TODAY'S HOTTEST APPLICATIONS

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
235/75R15	105T		12	28.9	9.3	2040@44	540AB	TH0610
LT235/75R15	104/101S	6	14	28.9	9.3	1985/1820@50		TH0423
LT235/75R15 OWL	104/101S	6	14	28.9	9.3	1985/1820@50		TH0427
30x9.50R15LT	104S	6	15	29.5	9.5	1984@50		TH0430
30x9.50R15LT OWL	104S	6	15	29.5	9.5	1984@50		TH0435
31x10.50R15LT	109S	6	15	30.5	10.6	2270@50		TH0450
31x10.50R15LT OWL	109S	6	15	30.5	10.6	2270@50		TH0452
LT215/85R16	115/112S	10	14	30.4	8.5	2680/2470@80		TH0428
LT235/85R16	120/116S	10	15	31.7	9.3	3042/2778@80		TH0429
LT225/75R16	115/112S	10	14	28.3	8.8	2680/2470@80		TH0431
245/75R16	111T		12	30.5	9.8	2405@44	540AB	TH0611
LT245/75R16	120/116S	10	15	30.5	9.8	3042/2278@80		TH0432
265/75R16	116T		12	31.7	10.5	2755@44	540AB	TH0612
LT265/75R16	123/120S	10	15	31.7	10.5	3415/3085@80		TH0433
LT285/75R16	126/123S	10	15	32.8	11.5	3750/3415@80		TH0436
235/70R16	106T		12	29.0	9.5	2095@44	540AB	TH0615
245/70R16XL	111T		12	29.5	9.8	2405@50	540AB	TH0620
255/70R16	111T		12	30.1	10.2	2405@44	540AB	TH0625
265/70R16	112T		12	30.6	10.7	2470@44	540AB	TH0630

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
LT235/80R17	120/117S	10	15	31.8	9.3	3085/2835@80		TH0650
LT245/75R17	121/118S	10	15	31.5	9.8	3195/2910@80		TH0655
245/70R17	110T		12	30.6	9.8	2335@44	540AB	TH0631
265/70R17	115T		12	31.7	10.7	2680@44	540AB	TH0635
LT265/70R17	121/118S	10	15	31.7	10.7	3195/2910@80		TH0434
285/70R17	117T		12	32.8	11.5	2835@44	540AB	TH0633
LT285/70R17	121/118S	10	15	32.8	11.5	3195/2910@80		TH0437
245/65R17	107T		12	29.5	9.8	2150@44	540AB	TH0640
265/65R17	112T		12	30.6	10.7	2470@44	540AB	TH0645
35X12.50 R17LT	121S	10	17	34.5	8.6	3195@65		TH0455
265/70R18	116T		12	32.6	10.7	2755@44	540AB	TH0517
275/65R18	116T		12	32.1	11.0	2755@44	540AB	TH0518
265/60R18	110T		12	30.5	10.7	2335@44	540AB	TH0522
275/60R20	115T		12	33.0	11.0	2680@44	540AB	TH0519
275/55R20XL	117T		12	31.9	11.2	2835@50	540AB	TH0521
285/55R20	115T		12	32.4	11.7	2680@44	540AB	TH0523
265/50R20	107T		12	30.5	10.9	2150@44	540AB	TH0525



# RANGER 007

## R601 | PREMIUM SUV

Quiet, smooth-riding and long-wearing 5 rib design. The tread is angled and siped for all-weather traction. Closed shoulder tread for confident cornering and handling. Designed for today's trucks, SUVs and crossovers. T, H and V rated for proper fitment and XL rated for proper load carrying capabilities.

### 60,000 MILES | NO QUESTIONS ASKED

SIZE	LI/SR	TD	OD	SW	MAX LOAD @ PSI	UTQG	STOCK#
205/70R14	98H	10	25.4	8.2	1655@50	560AA	TH0316
215/75 R15	100T	11	27.7	8.5	1765@44	560AA	TH0303
225/75R15	102T	11	28.3	8.8	1875@44	560AA	TH0305
235/75R15XL	109T	11	28.9	9.3	2270@50	560AA	TH0471
205/70R15	96H	10	26.3	8.2	1565@44	560AA	TH0318
215/70R15	98H	10	26.9	8.7	1655@44	560AA	TH0320
225/70R15	100H	11	27.4	9.0	1765@44	560AA	TH0322
235/70 R15	103H	11	28.0	9.5	1930@44	560AA	TH0323
225/75R16XL	108T	11	29.3	8.8	2205@50	560AA	TH0306
245/75R16	111T	11	30.5	9.8	2405@44	560AA	TH0307
265/75R16	116T	11	31.7	10.5	2755@44	560AA	TH0310
215/70R16	100H	11	27.9	8.7	1765@44	560AA	TH0324
225/70R16	103H	11	28.4	9.0	1930@44	560AA	TH0326
235/70R16	106H	11	29.0	9.5	2095@44	560AA	TH0328
245/70R16	111H	11	29.5	9.8	2405@50	560AA	TH0330
255/70R16	111H	11	30.1	10.2	2205@44	560AA	TH0331
265/70R16 OWL	112H	11	30.63	10.7	1120@44	560AA	TH0374
265/70R16	112H	11	30.6	10.7	2470@44	560AA	TH0370
215/65R16XL	102H	11	27.0	8.7	1875@50	560AA	TH0387



47  
SIZES

STRONG UTQG RATINGS

COMPLETE SIZE RANGE

14"/20"

FOR TODAY'S FASTEST GROWING MARKET SEGMENTS-CUVs

SIZE	LI/SR	TD	OD	SW	MAX LOAD @ PSI	UTQG	STOCK#
235/70R17	111H	11	30.0	9.5	2405@50	560AA	TH0376
245/70R17	110H	11	30.6	9.8	2335@44	560AA	TH0378
265/70R17	115H	11	31.7	10.7	2680@44	560AA	TH0379
225/65R17	102H	11	28.5	9.0	1875@44	560AA	TH0380
235/65R17	108H	11	29.1	9.5	2205@50	560AA	TH0382
245/65R17	111H	11	29.5	9.8	2405@50	560AA	TH0384
265/65R17 OWL	112H	11	30.55	10.7	1120@44	560AA	TH0377
265/65R17	112H	11	30.6	10.7	2470@44	560AA	TH0372
285/65R17	116H	11	31.6	11.5	2755@44	560AA	TH0373
225/60R17	99H	11	27.6	9.0	1710@44	560AA	TH0387
235/60R17	102H	11	28.1	9.5	1875@44	560AA	TH0385
225/55R17	101H	11	26.8	9.2	1820@50	560AA	TH0388
255/70R18	113H	11	32.1	10.2	2535@44	560AA	TH0371
265/70R18	116H	11	32.6	10.7	2755@44	560AA	TH0375
255/65R18	111H	11	31.1	10.2	2405@44	560AA	TH0391
275/65R18	116H	11	32.1	11	2755@44	560AA	TH0389
225/60R18	100H	11	28.6	9.0	1765@44	560AA	TH0393
235/60R18XL	107V	11	29.1	9.5	2150@50	560AA	TH0395
245/60R18	105V	11	29.6	9.8	2040@44	560AA	TH0397
265/60R18	110H	11	30.5	10.7	2335@44	560AA	TH0390
285/60R18	116V	11	31.5	11.5	2755@44	560AA	TH0398
225/55R18	98V	11	27.8	9.2	1655@44	560AA	TH0399
235/55R18	104V	11	28.2	9.7	1985@50	560AA	TH0392
255/55R18	109V	11	29.0	10.4	2270@50	560AA	TH0394
275/60R20	115H	11	33.0	11.0	2680@44	560AA	TH0400
275/55R20	117V	11	31.3	11.7	2835@44	560AA	TH0657
265/50R20	107V	11	30.5	10.9	2150@44	560AA	TH0396
285/50R20	112V	11	31.3	11.7	2470@44	560AA	TH0658



# TRAC GRIP M/T

## R408 | PREMIUM MUD TERRAIN

A maximum-traction on-/off-road radial with an aggressive attitude. The open and tiered tread block elements ensure maximum traction in extreme conditions. Available in 16" through 22" applications to fit today's most popular trucks and SUVs. The Q-rating along with the 10-ply rating ensures the necessary load carrying capacity.



SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
LT235/75R15	104/101Q	6	19	29.1	9.3	1985/1820@50	TH2467
30x9.50R15LT	104Q	6	19	29.8	9.5	1985@50	TH2475
31x10.50R15LT	109Q	6	19	30.8	10.6	2270@50	TH2463
33x12.50R15LT	108Q	6	21	32.8	12.5	2205@35	TH2465
LT235/85R16	120/116Q	10	19	32.0	9.3	3085/2755@80	TH2453
LT245/75R16	120/116Q	10	19	30.7	9.8	3085/2755@80	TH2455
LT265/75R16	123/120Q	10	19	31.9	10.5	3415/3085@80	TH2457
LT285/75R16	126/123Q	10	19	33.1	11.3	3750/3415@80	TH2459
LT245/75R17	121/118Q	10	19	31.7	9.8	3195/2910@80	TH2471
LT265/70R17	121/118Q	10	19	31.9	10.7	3195/2910@80	TH2461
LT285/70R17	121/118Q	10	19	33.0	11.5	3195/2910@80	TH2473
LT295/70R17	121/118Q	10	21	33.4	11.0	3195/2910@80	TH2454
35x12.50R17LT	121Q	10	21	34.8	12.5	3195@65	TH2466
LT275/70R18	125/122Q	10	19	33.5	11.8	3640/3305@80	TH2472
33x12.50R18LT	118Q	10	21	32.8	12.5	2910@65	TH2477
35x12.50R18LT	123Q	10	21	34.8	12.5	3415@65	TH2478
33x12.50R20LT	114Q	10	19	32.8	12.5	2600@65	TH2480
35x12.50R20LT	121Q	10	21	34.8	12.5	3195@65	TH2479
37x12.5R20LT	126	10	21	36.8	12.5	3750@65	TH2485
37x13.5R22LT	123	10	21	36.8	13.6	3415@65	TH2487
35x12.50R22LT	117Q	10	21	34.8	12.5	2835@65	TH2483

3-Ply sidewall for larger sizes where applicable.



## new TOURING CUV

All-Season Silica-Based compound improves wet and dry traction and provides long wearing durability. Proven tread design ensures quick and efficient water evacuation and traction in all conditions.

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
235/70R16	106T	12	29.0	9.5	2094@44	480AB	TH2205
235/70R16 OWL	106T	12	29.0	9.5	2094@44	480AB	TH2206
245/70R16	107T	12	29.5	9.8	2149@44	480AB	TH2210
245/70R16 OWL	107T	12	29.5	9.8	2149@44	480AB	TH2211
255/70R16	111T	12	30.1	10.2	2403@44	480AB	TH2215
255/70R16 OWL	111T	12	30.1	10.2	2403@44	480AB	TH2216
265/70R16	112T	12	30.6	10.7	2469@44	480AB	TH2220
265/70R16 OWL	112T	12	30.6	10.7	2469@44	480AB	TH2221
245/70R17	110T	12	30.6	9.8	2337@44	480AB	TH2225
245/70R17 OWL	110T	12	30.6	9.8	2337@44	480AB	TH2226
265/70R17	115T	12	31.7	10.7	2679@44	480AB	TH2230
265/70R17 OWL	115T	12	31.7	10.7	2679@44	480AB	TH2231
225/65R17	102H	12	28.5	9.0	1875@44	480AB	TH2233
235/65R17XL	108H	12	29.1	9.5	2205@50	480AB	TH2238
245/65R17	107T	12	29.5	9.8	2149@44	480AB	TH2250
245/65R17 OWL	107T	12	29.5	9.8	2149@44	480AB	TH2251
265/65R17	112T	12	30.6	10.7	2469@44	480AB	TH2255
265/65R17 OWL	112T	12	30.6	10.7	2469@44	480AB	TH2256
255/65R18	111T	12	31.1	10.2	2405@44	480AB	TH2253



## new COMMERCIAL CLT

Commercial Grade light truck tire with multi-ply casing construction to handle heavy work loads. Double steel belted plies provide puncture resistance and durability.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
LT215/85R16	115/112Q	10	14	30.4	8.5	2680/2470@80	TH2000
LT235/85R16	120/116Q	12	14	31.7	9.3	3042/2778@80	TH2010
LT225/75R16	115/112Q	11	14	29.3	8.8	2680/2470@80	TH2020
LT245/75R16	120/116Q	13	14	30.5	9.8	3042/2778@80	TH2030
LT265/75R16	123/120Q	14	15	31.7	10.5	3415/3085@80	TH2040
LT245/75R17	121/118Q	18	15	31.5	9.8	3195/2910@80	TH2041
LT245/70R17	119/116Q	17	15	31.5	9.8	3000/2755@80	TH2042
LT265/70R17	121/118Q	16	15	31.7	10.7	3195/2910@80	TH2044
LT275/70R18	125/122Q	15	15	33.2	11.0	3640/3305@80	TH2046





# ST RADIAL

## R501 | ST TRAILER RADIAL

Reliable 5 Rib design for ST applications. Available in 13" thru 16" in 6, 8, 10 and 12 ply ratings for a wide variety of trailering needs.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
ST175/80R13	91/87L	6	9	24.0	7.0	1360/1200@50	TH0480
ST205/75R14	100/96L	6	9	26.1	8.0	1760/1570@50	TH0484
ST205/75R14	105/101L	8	9	26.1	8.0	2040/1820@65	TH0485
ST215/75R14	102/98L	6	9	26.7	8.5	1870/1650@50	TH0486
ST205/75R15	101/97L	6	9	27.1	8.0	1820/1610@50	TH0488
ST205/75R15	107/102L	8	9	27.1	8.0	2150/1870@65	TH0489
ST225/75R15	113/108L	8	9	28.3	8.8	2450/2200@65	TH0490
ST225/75R15	117/112L	10	9	28.3	8.8	2830/2470@80	TH0491
ST235/80R16	123/119L	10	10	30.8	9.3	3420/3000@80	TH0482
ST235/80R16	125/121L	12	10	30.8	9.3	3630/3190@95	TH0483



# RANGER

## R402 | COMMERCIAL

Quiet smooth riding and long wearing with chevron tread design. Engineered for light truck applications requiring 6 and 8 ply rating. Q, R and S rated for proper fitment and load carrying capacity.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
195/70R15C	104/102R	8	12	25.8	7.9	1985/1875@65	TH0312
205/70R15C	106/104Q	8	12	26.3	8.2	2094/1984@65	TH0413
215/70R15C	106/104S	6	12	26.9	8.7	2094/1984@55	TH0415
215/70R15C	109/107R	8	12	26.9	8.7	2270/2150@65	TH0416
225/70R15C	112/110R	8	12	27.4	9.0	2470/2335@65	TH0418
205/75R16C	110/108R	8	12	28.1	8.0	2335/2205@69	TH0419
215/75R16C	113/111R	8	12	28.7	8.5	2535/2405@69	TH0421
225/75R16C	116/114R	8	12	29.3	8.8	2755/2600@69	TH0422
205/65R16C	107/105R	8	12	26.5	8.2	2150/2040@69	TH0424
215/65R16C	109/107R	8	12	27.0	8.7	2270/2150@69	TH0425
235/65R16C	115/113R	8	12	28.0	9.4	2680/2532@69	TH0426



# CITY

## R202 | COMPACT CAR RADIAL

The CITY R202 is designed with a smooth riding 4-rib tread pattern for economical compact cars.

SIZE	LI/SR	TD	OD	SW	MAX LOAD @PSI	UTQG	STOCK#
155/70R12	73T	9	20.6	6.2	805@44	240AA	TH0002
155/70R13	75T	9	21.6	6.2	853@44	300AB	TH0004
155/80R13	79T	9	22.8	6.2	963@44	300AB	TH0006
165R13	82S	10	23.4	6.5	1047@44	240AA	TH0008



# RANGER

## R200 | COMMERCIAL

The R200 is a speciality load carrying commercial tire in a long-wearing 4-rib commercial design.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
155R12C	88/86R	8	10	21.7	6.2	1235/1170@65	TH0500



# RANGER

## R101 | COMMERCIAL

The Ranger R101 has a 5-rib tread design engineered to meet the need of specific applications. The R101 is designed to deliver under all conditions.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
165R13C	94/92N	8	10	23.5	6.6	1480/1390@65	TH0301
185R14C	102/100Q	8	11	25.6	7.4	1874/1764@65	TH0304
195R14C	106/104P	8	11	26.2	7.8	2094/1984@65	TH0308
205R14C	109/107P	8	11	27.0	8.2	2505/2194@65	TH0309
195R15C	106/104P	8	11	27.2	7.8	2094/1984@65	TH0315
205R16C	110/108R	8	12	29.0	8.2	2335/2205@65	TH0317



# RANGER

## R403 | COMMERCIAL

The Ranger R403 has a 5-rib tread design engineered to meet the need of specific applications. The R403 is designed to deliver under all conditions.

SIZE	LI/SR	PLY	TD	OD	SW	MAX LOAD @PSI	STOCK#
225/70R15C	109/107S	6	12	27.4	9.0	4542/4299@55	TH0420
245/70R16C	107S		13	29.5	9.8	2149@44	TH0417



THUNDERER

NO QUESTIONS ASKED  
25/365  
WARRANTY

FIRST 25% OF TREAD  
LIFE OR ONE YEAR  
FROM DATE OF  
PURCHASE, WHICHEVER  
COMES FIRST.

WARRANTY

THUNDERER Limited Warranty for:  
P-Metric, Light Truck, Auto Passenger  
and Performance Tires and ST Radials.

WHO IS ELIGIBLE?

- Eligibility is contingent on meeting all the following criteria:
- Your THUNDERER tires were purchased on or after January 1, 2012
  - Your THUNDERER tires are used ONLY on the vehicle on which they were originally installed in accordance with vehicle manufactures designations found in the vehicles owners manual.
  - You are the owner or authorized agent of NEW THUNDERER P-Metric, Light Truck, Auto Passenger and Performance Tires and ST Radials.  
(Light Truck tires are defined as all tires with the sidewall identification "LT".)

WHAT IS COVERED AND FOR HOW LONG?

**FREE TIRE REPLACEMENT PERIOD**

If an eligible Thunderer brand passenger or light truck tires and ST Radials becomes unserviceable from a condition other than those listed below during the first 25% of usable tread wear or 1 year from date of purchase (whichever comes first) it will be credited back in the full amount of the original price.

**PRORATED ADJUSTMENT**

Tires not eligible for the free replacement that are removed from service due to a covered warranty condition will be replaced with a comparable new THUNDERER tire on a prorated basis for a period of five (5) years from the date of the original new tire purchase or when the tread-wear indicators become visible (worn to 2/32"), whichever occurs first.

**WHAT IS A COMPARABLE TIRE?**

A "comparable" tire may be either the same line and pattern of tire or, in the event that the tire is not available, a tire of the same basic construction and quality with a different sidewall or tread configuration. If a higher-priced tire is accepted as replacement, the difference in price will be at an additional charge to you.

Any THUNDERER replacement tire provided pursuant to this warranty will be covered by the THUNDERER warranty in effect at the time of replacement.

**TIRE MILEAGE WARRANTY**

The Thunderer brand tires listed below are warranted against wear out up to the mileage coverage shown in this section, even though the actual mileage you may get from your tires may vary because of driving habits and road conditions. Subject to the items originally covered below, if one of the tires listed in this warranty wears out before the listed mileage American Omni Trading will adjust the tire on a pro-rata basis. "Wear Out" means that the tire's tread has worn evenly down to the tread wear indicator's (2/32nds of an inch of tread remaining). "Pro-Rata" for this Tread Wear Out Coverage is measured by the odometer readings at the time of the tire's purchase, as printed on the original tire sales invoice, and at the time of replacement. In addition, you must present a completed rotation schedule contained in the original owner's copy of the tire's Limited Warranty / Tire Guide / Adjustment Policy.

TIRE(S) that have not been rotated at least every 6000 miles as evidenced by a completed rotation schedule are excluded.

TIRE(S) in service for more than 60 months regardless of mileage are not covered.

**TREAD LIFE LIMITED WARRANTY**

THUNDERER replacement tire listed below is warranted against pre-mature tread wear-out based on the following table:

THUNDERER / MACH I	60,000 Mile Limited Warranty
THUNDERER / MACH II	60,000 Mile Limited Warranty
THUNDERER / MACH III	40,000 Mile Limited Warranty
THUNDERER / MACH IV	60,000 Mile Limited Warranty
THUNDERER / RANGER 007	40,000 Mile Limited Warranty

The tread life limited warranty applies ONLY to you if you are the Original Purchaser and the tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. The tread life limited warranty does not apply to the following conditions: Tires used in commercial applications including but not limited to, police, taxi service, national account, government and contract sales. Tires supplied as original equipment. Tires that are installed on any vehicle other than the vehicle on which they were originally installed.

This TIRE MILEAGE WARRANTY DOES NOT include mounting, balancing, TPMS and applicable taxes and fees, which remain the customer's obligation and is NOT transferable.

You will receive a credit based upon the dealers replacement price based on the percentage of actual mileage driven to the mileage covered. Your replacement cost will be determined by dividing the actual mileage driven by the miles warranted and multiplying the result times the current selling price.

**ITEMS NOT COVERED:**

- **Ride / Vibration** - Any ride / vibration complaint after the first 1/32nd of an inch of tread wear.
- **Improper Operation or Maintenance** - Includes, but not limited to improper inflation, or improper load/speed practices. In addition, improper tire rotation, wear due to improper vehicle alignment and tire alteration.
- Deliberate abuse or vandalism.

**OWNER'S OBLIGATIONS**

You must rotate your tires with the prescribed rotation patterns as recommended by either your vehicle owners manual or your authorized THUNDERER Dealer.

When making a claim under the tread life limited warranty, you must present the original tire purchase invoice complete with tire description, mileage and the date the tire(s) were installed.

You must present the tire to be adjusted to a THUNDERER Retailer. Tires replaced as an adjustment become the property of THUNDERER Tires.

You must pay any other applicable taxes and government-mandated charges on the services you order at the time of adjustment relating to any unique applications requiring mounting, demounting or balancing.

No claim will be recognized unless submitted on an approved claim form (supplied by a THUNDERER retailer) completely filled out and where you, the owner, or your authorized agent presented the tire for adjustment.

**LIMITATIONS**

This limited warranty is applicable only in the United States and Canada.

**WHAT ARE YOUR LEGAL RIGHTS?**

No Representative or Dealer has authority to make any representation, promise or agreement on behalf of THUNDERER, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of tire manufacturer. Under no circumstances is this warranty a representation that a tire failure cannot occur. This warranty gives you specific legal rights and you may also have other rights that vary from state to state or province to province.

DISCLAIMER: THIS WARRANTY IS IN LIEU OF, AND THUNDERER TIRES HEREBY DISCLAIMS, ANY AND ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND NO OTHER WARRANTY OR REPRESENTATION OF ANY KIND IS MADE BY THUNDERER TIRES OR SHALL BE IMPLIED BY LAW.

LIMITATION OF DAMAGES: IN NO EVENT AND UNDER NO CIRCUMSTANCE SHALL THUNDERER TIRES BE LIABLE TO THE BUYER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL, LOST PROFIT, LOSS OF BUSINESS, LOSS OF GOODWILL OR REPUTATION, PUNITIVE OR OTHER DAMAGE, COST (INCLUDING FOR REPLACEMENT TRANSPORTATION), EXPENSE OR LOSS OF ANY KIND. SOME STATES AND PROVINCES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

**HOW DO YOU OBTAIN AN ADJUSTMENT?**

You must present the tire to be adjusted to an authorized THUNDERER service facility. Tires replaced on an adjustment basis become the property of THUNDERER Tires.

You must submit your claim on an approved claim form supplied by an authorized THUNDERER service facility. The form must be filled out completely, where you, the owner, or your authorized agent presented the tire for adjustment.

**THUNDERER Tire Care and Maintenance Guide**

To ensure satisfactory mileage and performance from your THUNDERER tires give them a simple but frequent (at least monthly) check for proper inflation along with even tread wear and inspect your tires for any presence of damage."

**MAINTAIN PROPER INFLATION PRESSURE**

Proper inflation pressure is essential for optimum tire performance, safety and fuel economy. Check for proper inflation pressure at least monthly while tires are cool, tires will warm up from use after a number of miles so its best to check before driving. Use a quality hand held accurate tire gauge. Its best to occasionally have your THUNDERER tires inspected by a professional tire shop, it is difficult to tell just by looking at radial tires whether they are under-inflated or over-inflated.

Furthermore, when operating a vehicle equipped with radial tires, it is difficult to notice when a tire has gone flat or nearly flat since the "feel" of the vehicle may not always change significantly.

\*Evidence of air loss or repeated under-inflation always requires expert inspection to determine the source of leakage and tire removal to determine repairability. To avoid injury, NEVER attempt to re-inflate a tire that has been run severely under-inflated.

Progressive air loss may result from a variety of conditions such as punctures, cuts, curbing, impacts or partial bead unsealing. Some installation or fitment causes for air loss are (1) incomplete bead seating, (2) tearing of the tire bead caused by a machine tool due to insufficient lubrication or improper adjustment, (3) leaking valve core or rubber valve components. These should be corrected or replaced when problems are detected and/or whenever tires are replaced.

Always maintain inflation pressure at the level recommended by the vehicle manufacturer as shown on the vehicle placard, on the vehicle certification label or in the vehicle owner's manual:

Under-inflation is the leading cause of tire failure and may result in severe cracking, component separation or complete loss of air. Under-inflation reduces tire load carrying capacity, allows for excessive sidewall flexing and increased rolling resistance, resulting in potential heat build-up and mechanical damage. Maintaining proper inflation pressure is the most important thing you can do to help promote tire safety, durability and maximize tread life.

Overinflation increases excess stiffness, which may deteriorate ride and generate unwanted vibration. Overinflation also increases the chances of impact damage.

**DON'T OVERLOAD YOUR VEHICLE**

The maximum load capacity stamped on the sidewalls of P-metric tires is reduced by 10 percent when used on a light truck, utility vehicle or trailer. Never fit P-metric tires to light trucks that specify LT-type replacement tires.



# ***THUNDERER***



**American Omni Trading Company**  
15354 Park Row  
Houston TX 77084

Corporate Phone | 281-600-TIRE  
[american-omni.com](http://american-omni.com)